





refer to SDHDC: R39 for mid size blocks

PRINCIPLE PRIVATE OPEN SPACE (PPOS) refer to SDHDC R41 and Table 8

> Gate, street address and letterbox to be off lane (as indicated) refer to Planning Controls Plan

Inter-allotment fencing to be max 1.8m high timber paling fencing or lapped and capped timber paling fencing.

If Colorbond is used, the profile must be Neetascreen or a mini orb profile colour "Basalt". refer to Ginninderry Design Requirements

## Return Boundary Fencing to Building Line or Side Fence

## Services

Refer to Block Disclosure Plan for location of service access to this block. Proposed Fencing and Courtyard Walls to integrate service ties and meters. **Optional - Corner Blocks** Maximum height 1.5m | Minimum setback 0m (50%) and 0.8m (50%) No fencing within 6m of the corner refer to Fencing Controls Plan

## **Construction and Finish**

Front Courtyard walls and fencing forward of the building line (where permitted) must be a combination of solid and semi-transparent elements that are constructed of the following:

- masonry or stonework;
- dressed hardwood timber; or
- powder-coated aluminium.
- Openings to be a minimum of 10mm.

refer to Fencing Control Plan and Ginninderry Design Requirements

## **BLOCK INFORMATION**

49 SECTION BLOCKS 5-9 TERRACE BLOCK HOUSING TYPE

REV DRAWN CHECKED APPROVED INFORMATION ON THIS PLAN IS TO BE USED AS A GUIDE ONLY FOR THE DESIGN PROCESS. APPROVED EDP PLANNING CONTROLS NEED TO BE CHECKED AGAINST PRECINCT CODE UPLIFTS. PLANS TO BE READ IN CONJUNCTION WITH THE TERRITORY PLAN ALONG WITH BLOCK DISCLOSURE PLANS AND THE GINNINDERRY DESIGN REQUIREMENTS TO CONFIRM ALL CURRENT CONTROLS PERTAINING TO YOUR BLOCK.



