




TIT

Ш田

留置

田間

LEGEND





Garage Location

Boundary Defined by SDHDC

Only one (1) Onsite Parking Space Required refer to Planning Controls Plan

Part of Integrated Development Parcel by Planning Controls Plan

INDICATIVE BUILDING FOOTPRINTS

(based on min. building setbacks ${\rm only}$ This does not take into account easements or building envelopes)



Lower Floor Level

Upper Floor Level

All Floor Level - Side and Rear Boundary - Screened All Floor Level - Side and Rear Boundary Unscreened

REV DRAWN CHECKED APPROVED **BLOCK INFORMATION** DATE A DZ AK CS 04/02/20 B AK AK CS 06/10/20 DO NOT SCALE OFF DRAWINGS. DIMENSIONS ARE IN METRES. STAGE 2R2 Ginninderry SCALE ZONE RZ3 INFORMATION ON THIS PLAN IS TO BE USED AS A GUIDE ONLY FOR THE DESIGN PROCESS, APPROVED EOP PLANNING CONTROLS NEED TO BE CHECKED AGAINST PRECENCT CODE UPLIFTS. PLANS TO BE READ IN CONJUNCTION WITH THE TERRITORY PLAN ALONG WITH BLOCK DISCLOSURE PLANS AND THE GINNDERRY DESIGN REQUIREMENTS TO CONFIRM ALL CURRENT CONTROLS PERTAINING TO YOUR BLOCK. 81 SECTION 1:250 @A3 1 - 10 BLOCKS BLOCK PLANNING CONTROLS TERRACE BLOCK HOUSING TYPE **BUILDING & SITING CONTROLS PLAN**

MINIMUM BOUNDARY SETBACKS

----- Single Dwelling Housing Development Code (SDHDC) front setbacks: refer to Rule11: Table 4 for compact block side and rear setbacks: refer to Rule 12: Table 7 for compact block Strathnairn Stage 2 EDP refer to the Planning Controls Plan Lower floor level - external wall or unscreened element Upper floor level (front setbacks) - external wall or unscreened element Upper floor level (side setbacks) - external wall (screened)



Articulation Elements (Articulation Zone) refer to Planning Controls Plan







PRIVATE OPEN SPACE (POS) refer to SDHDC: R40 for compact blocks

PRINCIPLE PRIVATE OPEN SPACE (PPOS) refer to SDHDC R41 and Table 8

building line

refer to EPSDD: Fences and Freestanding Walls Factsheet 2014

Construction and Finish

Inter-allotment fencing to be max 1.8m high timber paling fencing or lapped and capped timber paling fencing.

If Colorbond is used, the profile must be Neetascreen or a mini orb profile colour "Basalt". refer to Ginninderry Design Requirements

Return Boundary Fencing to Building Line or Side Fence

Services

Refer to Block Disclosure Plan for location of service access to this block.

Proposed Fencing and Courtyard Walls to integrate service ties and meters.

refer to Fencing Controls Plan



Corner Identified for Corner Block Control refer to Fencing Controls Plan

Optional - Corner Blocks - c -

Maximum height 1.5m | Minimum setback 0m (50%) and 0.8m (50%) No fencing within 6m of the corner refer to Fencing Controls Plan

Construction and Finish

Front Courtyard walls and fencing forward of the building line (where permitted) must be a combination of solid and semi-transparent elements that are constructed of the following:

- masonry or stonework;
- dressed hardwood timber; or
- powder-coated aluminium.
- Openings to be a minimum of 10mm.

refer to Fencing Control Plan and Ginninderry Design Requirements

