


	Ŵ	251 < 350 351 < 599 600 < 800 > 801	4,000 6,000 10,000	INDICATIVE BUILDING FOOTPRINTS (based on min. building setbacks. This does not take into account site coverage or building envelopes) Lower Floor Level	
					Upper Floor Level - Side and Rear Boundary - Screened
				\sim	Upper Floor Level - Side and Rear Boundary - Unscreened
BLOCK INFORMATION	REV DRAWN CHECKED	APPROVED DATE			
STAGE 1E	B DC,AM JM	JM 25/09/24		$(\mathbf{\Gamma})$	N.
ZONE RZ3 SECTION BE BLOCK i	DO NOT SCALE OFF DRAWINGS, DIMENSIONS, INFORMATION ON THIS PLAN IS TO BE USED AS FROCESS, APPROVED EDP PLANNING CONTRO		scale 1:250 @A4	\bigcirc	Ginninderry
CLASSIFICATION Mid-Sized HOUSING TYPE Single Dwelling	DISTRUCT TECHNICAL SPECIFICATIONS UPUETS FLANS TO BE READ IN COMJUNCTION WITH THE TERRITORY PLAN ALONG WITH BLOCK DISCLOSURE PLANS AND THE ORNINOESKY DESIGN REQUREMENTS TO COMPRIM ALL CURRENT CONTROLS PERTAINING TO YOUR BLOCK.			10	BLOCK PLANNING CONTROLS BUILDING & SITING CONTROLS PLAN





PRINCIPLE PRIVATE OPEN SPACE

Refer to Planning (Exempt Development) - SDHDCD

Block Boundary	—— F—C —
Garage Location	n N N
Boundary Type As defined by Territory Plan Definitions	FC C

Side, Rear and Boundaries Fronting Rear Lane Maximum height 1.8m from NGL] Minimum setback 0m (100%) | Min 1m behind the front building line

Construction and Finish

Inter-allotment fencing to be max 18m high timber paling fencing or lapped and capped timber paling fencing. If Colorbond is used, the profile must be Neetascreen or Miniscreen and colour "Jasper". *Refer to Ginninderry Design Requirements (Macnamara)*

Return Boundary Fencing to Building Line or Side Fence

Mandatory Fencing Type F2: Refer to the EDP Planning Controls Plans Mandatory height: 18m Minimum Boundary Length: 50% Minimum setback from boundary: Nil

Optional - Front Boundary Courtyard Wall:

Refer to Planning (Exempt Development) - SDHDCD Maximum height: 18m Minimum setback: 50% of minimum building setback Maximum length: 50% of boundary length

Construction and Finish

No fances are permitted forward of the building line. Courtyard walls are permitted in instances where spacified in the Belconnen District Specifications & Residential Zanes Specifications (whichever is applicable). Courtyard wall must be a combination of solid and semi-transparent elements that are constructed of the following: masonry or stonework; dressed hardwood timber; or powder-coated aluminium. Openings to be a minimum of 10mm. Refer to Fencing Control Plan and Ginninderry Design Requirements (Macnamara)

