

STREET



SITE LOCATION Macnamara Stage 2 Conservation Edge Site COVERAGE Refer to Planning (Seempt Development) - SDHDCD

PRINCIPLE PRIVATE OPEN SPACE

Refer to Planning (Exempt Development) - SDHDCD

Garage Location

Boundary Type

s defined by Territory Plan Definitions

Inter-Allotment Fencing: side and rear boundaries

Maximum height 1.8m from NGL. | Minimum setback 0m (100%)
Min 1.0m behind the front building line

Construction and Finish

Inter-allotment fencing to be max L8m high timber paling fencing or lapped and capped timber paling fencing. If Colorbond is used, the profile must be Neetascreen or Miniscreen and colour "Jasper". Refer to Ginninderry Design Requirements (Macnamara)

Return Boundary Fencing to Building Line or Side Fence

Fencing Type F4: Refer to the EDP Planning Controls Plans Mandatory height L5m Minimum Boundary Length: 50% Minimum setback from boundary: Nil

Street facing side gate/fence:

Minimum 1.0m behind the front building line Maximum height 1.8m

Maximum height 1.8m Construction and Finish:

To be open form (min. 10mm gaps), either treated hardwood, powdercoated aluminium. Refer to Ginninderry Housing Design Requirements (Macnamara,

Construction and Finish

No fences are permitted forward of the building line. Courtyard walls are permitted in instance where specified in the Belconnen District Specifications & Residential Zones Specifications (hubbarous in pendiotable).

Courtyard wall must be a combination of solid and semi-transparent elements that are constructed of the following: masonry or stonework; dressed hardwood timber, or powder-coated aluminium.

Openings to be a minimum of 10mm.

Refer to Fencing Control Plan and Ginninderry Design Requirements (Macnamara)

BLOCK INFORMATION







